

## BLANCOTHERM

### BLANCOTHERM K synthetic

BLANCOTHERM K, unheated . . . . .38  
 BLANCOTHERM K, heated/convection-heated .39  
 Accessories for BLANCOTHERM K . . . . .40

### BLANCOTHERM E stainless steel

BLANCOTHERM E, unheated . . . . .43  
 BLANCOTHERM E, heated . . . . .43  
 BLANCOTHERM E, cooled . . . . .44  
 Accessories for BLANCOTHERM E . . . . .44











# BLANCOTHERM synthetic

- of food-resistant polypropylene
- dishwasher-safe



## BLT synthetic, unheated


Illustration	Model	Designation	Capacity	Dimensions L x W x H (mm)	Weight (kg)	Order No.
BLT 160 K (shown with accessories: GN containers) 	<u>BLT 160 K</u>	<b>BLANCOTHERM 160 K</b> with lid	GN 1/1-100 or their subdivisions	630 x 425 x 230 mm	7 kg	<b>566 240</b>
BLT 320 ECO 	<u>BLT 320 ECO</u>	<b>BLANCOTHERM 320 ECO</b> with clamping lid, with moulded skids and handles	GN 1/1-200 or their subdivisions	620 x 415 x 345 mm	7 kg	<b>564 650</b>
BLT 320 K 	<u>BLT 320 K</u>	<b>BLANCOTHERM 320 K</b> with lid	GN 1/1-200 or their subdivisions	630 x 425 x 340 mm	8 kg	<b>566 241</b>
BLT 420 K (shown with accessories: GN containers) 	<u>BLT 420 K</u>	<b>BLANCOTHERM 420 K</b> with hinged door	2 x GN 1/1-150 or their subdivisions  11 pairs of support ledges with spacing of 31 mm	630 x 430 x 490 mm	10 kg	<b>564 652</b>
BLT 620 KUS (shown with accessories: GN containers) 	<u>BLT 620 KUS</u>	<b>BLANCOTHERM 620 KUS</b> with lid, side lock	3 x GN 1/1-150 or their subdivisions  12 pairs of support ledges with spacing of 39 mm	630 x 425 x 660 mm	13.5 kg	<b>566 243</b>
BLT 620 KUF (shown with accessories: GN containers) 	<u>BLT 620 KUF</u>	<b>BLANCOTHERM 620 KUF</b> with hinged door, that can be opened to an angle of 270°	3 x GN 1/1-150 or their subdivisions  12 pairs of support ledges with spacing of 39 mm	670 x 445 x 660 mm	13.5 kg	<b>564 365</b>
BLT 620 KV (shown with accessories: GN containers) 	<u>BLT 620 KV</u>	<b>BLANCOTHERM 620 KV</b> with lid, top lock	3 x GN 1/1-150 or their subdivisions  12 pairs of support ledges with spacing of 39 mm	630 x 425 x 660 mm	13.5 kg	<b>564 358</b>
BLT 620 KF (shown with accessories: GN containers) 	<u>BLT 620 KF</u>	<b>BLANCOTHERM 620 KF</b> with lid, side lock, with castors that comply with DIN 18867-8, synthetic, 4 steering castors, 2 of which have brakes	3 x GN 1/1-150 or their subdivisions  12 pairs of support ledges with spacing of 39 mm	630 x 425 x 830 mm	18 kg	<b>564 350</b>

# BLANCOTHERM synthetic







- of food-resistant polypropylene
- dishwasher-safe (convection-heated BLT without door only)



## BLT synthetic, unheated

Illustration	Model	Designation	Capacity	Dimensions L x W x H (mm)	Rating/ conn. load	Weight (kg)	Order No.
 <p>BLT 720 K (shown with accessories: wire support ledges, baking trays)</p>	<u>BLT 720 K</u>	<b>BLANCOTHERM 720 K</b> with snap-on lid, top rotary lock	Baskets or baking trays 600 x 400 mm  Support ledges available as ac- cessories	725 x 565 x 730 mm		23.5 kg	<b>568 752</b>

## BLT synthetic, heated






 <p>BLT 320 KB (shown with accessories: GN containers)</p>	<u>BLT 320 KB</u>	<b>BLANCOTHERM 320 KB</b> heated, with power on/off indicator, max. temperature +90 °C, with lid, inside container of CNS 18/10	GN 1/1-200 or their subdivisions	645 x 425 x 375 mm	0.4 kW 220-240 V 50-60 Hz	13.5 kg	<b>566 242</b>
 <p>BLT 320 KBR (shown with accessories: GN containers)</p>	<u>BLT 320 KBR</u>	<b>BLANCOTHERM 320 KBR</b> with digital temperature control for adjusting the interior container temperature in 1° increments from +40 °C to +95 °C, with lid, inside container of CNS 18/10	GN 1/1-200 or their subdivisions	645 x 425 x 375 mm	0.4 kW 220-240 V 50-60 Hz	13.5 kg	<b>572 228</b>
 <p>BLT 420 KBUH</p>	<u>BLT 420 KBUH</u>	<b>BLANCOTHERM 420 KBUH</b> convection-heated, with power on/off indicator, max. temperature +90 °C, with hinged door	2 x GN 1/1-150 or their subdivisions 11 pairs of support ledges with spacing of 31 mm	690 x 437 x 490 mm	0.2 kW 220-240 V 50-60 Hz	16 kg	<b>572 534</b>
 <p>BLT 420 KBRUH</p>	<u>BLT 420 KBRUH</u>	<b>BLANCOTHERM 420 KBRUH</b> convection-heated, with digital temperature control for adjusting the interior temperature in 1° increments from +40 °C to +85 °C, with hinged door	2 x GN 1/1-150 or their subdivisions 11 pairs of support ledges with spacing of 31 mm	690 x 437 x 490 mm	0.2 kW 220-240 V 50-60 Hz	16 kg	<b>572 535</b>
 <p>BLT 620 KBUH</p>	<u>BLT 620 KBUH</u>	<b>BLANCOTHERM 620 KBUH</b> convection-heated, with power on/off indicator, max. temperature +90 °C, with hinged door	3 x GN 1/1-150 or their subdivisions  12 pairs of support ledges with spacing of 39 mm	700 x 445 x 660 mm	0.2 kW 220-240 V 50-60 Hz	19.5 kg	<b>572 536</b>
 <p>BLT 620 KBRUH</p>	<u>BLT 620 KBRUH</u>	<b>BLANCOTHERM 620 KBRUH</b> convection-heated, with digital temperature control for adjusting the interior temperature in 1° increments from +40 °C to +85 °C, with hinged door	3 x GN 1/1-150 or their subdivi- sions  12 pairs of support ledges with spacing of 39 mm	700 x 445 x 660 mm	0.2 kW 220-240 V 50-60 Hz	19.5 kg	<b>572 537</b>

# Accessories for BLANCOTHERM synthetic

\* corrosion-resistant pursuant to DIN 18867-8

# accessories

## Accessories



Illustration	Model	Designation	For models	Dimensions L x W x H (mm)	Weight/ load cap. (kg)	Castors dia. 125 mm	Order No.
	<u>ROLA 13</u>	<b>Serving dolly</b> with lid receptacle	1x BLT 160 K or 1x BLT 320 K/KB/KBR/ECO	592 x 425 x 535 mm	10 kg	4 steering castors, 2 of which have brakes	
						<b>synthetic *</b>	<b>572 341</b>
						<b>galvanized steel</b>	<b>572 342</b>
	<u>ROLA 23</u>	<b>Serving dolly</b> with lid receptacle	2x BLT 160 K or 2x BLT 320 K/KB/KBR/ECO	945 x 592 x 535 mm	19 kg	4 steering castors, 2 of which have brakes	
						<b>synthetic *</b>	<b>572 343</b>
						<b>galvanized steel</b>	<b>572 344</b>
	<u>ROL 6x4</u>	<b>Serving dolly</b>	4x BLT 160 K or 3x BLT 320 K/KB/KBR/ECO or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	542 x 432 x 212 mm	8 kg	4 steering castors, 2 of which have brakes	
						<b>synthetic *</b>	<b>572 339</b>
						<b>galvanized steel</b>	<b>572 340</b>
	<u>ROLLI-100</u>	<b>Serving dolly</b>	4x BLT 160 K or 3x BLT 320 K/KB/KBR/ECO or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	650 x 450 x 165 mm	4.5 kg 130 kg	<b>galvanized steel</b> 4 steering castors, 2 of which have brakes, dia. 100 mm	<b>568 236</b>
	<u>ROLLI-125</u>	<b>Serving dolly</b>	4x BLT 160 K or 3x 320 K/KB/KBR/ECO or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	650 x 450 x 190 mm	4.5 kg 130 kg	<b>synthetic *</b> 4 steering castors, 2 of which have brakes	<b>568 237</b>
not shown	<u>Plug-in tray holders</u>	<b>Plug-in tray holders</b> for locking EN and GN tray sets	ROLLI-100 or ROLLI-125				<b>568 925</b>
not shown	<u>Push bar</u>	<b>Push bar</b> for better maneuvering	ROLLI-100 or ROLLI-125				<b>568 926</b>
	<u>BTA 3</u>	<b>Transport and serving trolley</b>  2 shelves: 940 x 700 mm  Clear height between shelves: 300 mm	2x BLT 160 K or 2x BLT 320 K/KB/KBR or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	1070 x 780 x 840 mm	31 kg	4 steering castors, 2 of which have brakes	
						<b>synthetic *</b>	<b>572 325</b>
						<b>galvanized steel</b>	<b>572 326</b>

## Accessories for BLANCOTHERM synthetic

\* corrosion-resistant pursuant to DIN 18867-8

# accessories

### Accessories

Illustration	Model	Designation	For models	Dimensions L x W x H (mm)	Weight/ load cap. (kg)	Castors dia. 125 mm	Order No.	
	<b><u>BTT 8x6</u></b>	<b>Platform trolley</b>	4x BLT 160 K or 3 x BLT 320 ECO/K/KB/KBR or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	605 x 780 x 840 mm	11 kg	2 fixed castors, 2 steering castors with brakes		
			Clear height of platform: 230 mm				<b>synthetic *</b>	<b>572 329</b>
							<b>galvanized steel</b>	<b>572 330</b>
	<b><u>BTT 10x8</u></b>	<b>Platform trolley</b>	8x BLT 160 K or 4 x BLT 320 ECO/K/KB/KBR or 2x BLT 420 K/KBUH/KBRUH or 2x BLT 620 K/KBUH/KBRUH	1045 x 780 x 840 mm	20 kg	2 fixed castors, 2 steering castors with brakes		
			Clear height of platform: 230 mm				<b>synthetic *</b>	<b>572 327</b>
							<b>galvanized steel</b>	<b>572 328</b>
not shown	<b><u>Tightening straps</u></b>	Tightening straps	Accessories for BTT 10 x 8				<b>572 374</b>	

### Accessories for BLT 720 K

not shown	<b><u>Rolli 720 CNS</u></b>	<b>Platform trolley</b> with push handle	1x BLT 720 K	686 x 615 x 977 mm	6 kg	<b>CNS *</b> 4 steering castors, 2 of which have brakes	<b>569 291</b>
	<b><u>Rolli 720-2</u></b>	<b>Platform trolley</b> round-tube construction	2x BLT 720 K	686 x 615 x 1276 mm	6 kg	<b>synthetic *</b> 4 steering castors, 2 of which have brakes	<b>569 317</b>
not shown	<b><u>Wire supports of CNS</u></b>	<b>Wire support</b> of CNS, for inserting baking trays and baskets, removable for cleaning	BLT 720 K	11 pairs of supports  with spacing of 55 mm	4.5 kg		<b>573 013</b>
not shown	<b><u>Synthetic support ledges</u></b>	<b>Support ledge</b> for inserting baking trays (max. height 20 mm), removable for cleaning	BLT 720 K	11 pairs of support ledges  with spacing of 55 mm	3.5 kg		<b>569 011</b>

# accessories

## Accessories




Illustration	Model	Designation	For models	Dimensions L x W x H (mm)	Weight (kg)	Order No.
	<u>Eutectic plate</u>	<b>Eutectic plate</b> (-3 °C) of synthetic, for inserting into synthetic or wire support ledges of BLT 720 K	BLT 720 K	600 x 400 x 20 mm	5.6 kg	<b>572 588</b>
	<u>Eutectic plate</u>	<b>Eutectic plate</b> (-12 °C) of CNS, Gastronorm-compatible	BLT 420 K/KBUH/KBRUH or BLT 620 K/KBUH/KBRUH	530 x 325 x 30 mm	5.6 kg	<b>564 756</b>
	<u>Eutectic plate</u>	<b>Eutectic plate</b> (-3 °C) synthetic, Gastronorm-compatible	BLT 420 K/KBUH/KBRUH or BLT 620 K/KBUH/KBRUH	530 x 325 x 30 mm	4.2 kg	<b>568 136</b>
			BLT 160 K or BLT 320 ECO/K/KB/KBR	483 x 283 x 36 mm	4.0 kg	<b>569 315</b>
 (shown with accessories: GN support bar)	<u>Slide-in frame</u>	<b>Slide-in frame</b> of CNS 18/10 suitable for Gastronorm containers up to 150 mm deep	BLT 420 K/KBUH/KBRUH or BLT 620 K/KBUH/KBRUH	530 x 325 x 156 mm	0.5 kg	<b>564 352</b>
	<u>ST 3</u>	<b>GN support bar</b> of CNS 18/10 for container combination, required with GN 1/4, 1/6 and 1/9	BLT 160 K or BLT 320 ECO/K/KB/KBR or slide-in frame	Length: 325 mm		<b>550 650</b>
	<u>ST 5</u>	<b>GN support bar</b> of CNS 18/10, with spring lock, for container combination, required with GN 1/4, 1/6 and 1/9	BLT 160 K or BLT 320 ECO/K/KB/KBR or slide-in frame	Length: 530 mm		<b>550 651</b>
	<u>Special pen</u>	<b>Special washable pen</b> for labeling menu cards	all BLT K			<b>564 361</b>
	<u>Menu card</u>	BLANCOTHERM <b>menu card</b> , blank	all BLT K	DIN A 6 (148 x 105 mm)		<b>564 353</b>
	<u>Set of menu cards 20x</u>	Set consisting of <b>20 menu cards</b> for BLANCOTHERM			<b>564 359</b>	
	<u>Set of menu cards 50x</u>	Set consisting of <b>50 menu cards</b> for BLANCOTHERM			<b>564 360</b>	
 (shown with accessories: menu cards)	<u>Menu card dispenser</u>	<b>Dispenser</b> for BLANCOTHERM menu cards, wire wall unit (Capacity: 50 cards)	all BLT K			<b>564 354</b>
 (shown with accessories: menu cards)	<u>Menu card box</u>	<b>Menu card box</b> for BLANCOTHERM menu cards (Capacity: 25 cards)	all BLT K			<b>564 355</b>

# BLANCOTHERM stainless steel





- With synthetic castors, corrosion-resistant in compliance with DIN 18867-8
- 125 mm dia., 2 fixed castors, 2 steering castors with locking brakes



## BLT stainless steel, unheated

Illustration	Model	Designation	Capacity	Dimensions L x W x H (mm)	Weight (kg)	Order No.
	<b>BLT 820 E</b>	<b>BLANCOTHERM 820 E</b> Food transport container of stainless steel, with hinged door, mobile	GN container up to a max. of 3 x GN 1/1-200  11 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 977 mm	56 kg	<b>572 515</b>
	<b>BLT 1020 E</b>	<b>BLANCOTHERM 1020 E</b> Food transport container of stainless steel, with hinged door, mobile	GN container up to a max. of 3 x GN 1/1-200 + 1 x GN 1/1-100  14 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 1150 mm	63 kg	<b>572 518</b>
	<b>BLT 1220 E</b>	<b>BLANCOTHERM 1220 E</b> Food transport container of stainless steel, with hinged door, mobile	GN container up to a max. of 5 x GN 1/1-200  20 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 1495 mm	83 kg	<b>572 520</b>

## BLT stainless steel, heated



Illustration	Model	Designation	Capacity	Dimensions L x W x H (mm)	Rating/ conn. load	Weight (kg)	Order No.
 CE	<b>BLT 820 EB</b>	<b>BLANCOTHERM 820 EB</b> Food transport container of stainless steel, heated, with hinged door, mobile, temperature range: +30 °C to +90 °C	GN container up to a max. of 3 x GN 1/1-200  11 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 977 mm	220-240 V AC 50-60 Hz 0.38 kW	59 kg	<b>572 516</b>
 CE	<b>BLT 820 EBTF</b>	<b>BLANCOTHERM 820 EBTF</b> Food transport container of stainless steel, heated, top and front loader, mobile, temperature range: +30 °C to +90 °C	GN container up to a max. of 3 x GN 1/1-200  11 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 1060 mm  Operating height: 977 mm	220-240 V AC 50-60 Hz 0.38 kW	61 kg	<b>572 517</b>
 CE	<b>BLT 1020 EB</b>	<b>BLANCOTHERM 1020 EB</b> Food transport container of stainless steel, heated, with hinged door, mobile, temperature range: +30 °C to +90 °C	GN container up to a max. of 3 x GN 1/1-200 + 1 x GN 1/1-100  14 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 1150 mm	220-240 V AC 50-60 Hz 0.38 kW	66 kg	<b>572 519</b>
 CE	<b>BLT 1220 EB</b>	<b>BLANCOTHERM 1220 EB</b> Food transport container of stainless steel, heated, with hinged door, mobile, temperature range: +30 °C to +90 °C	GN container up to a max. of 5 x GN 1/1-200  20 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 815 x 1495 mm	220-240 V AC 50-60 Hz 0.76 kW	86 kg	<b>572 521</b>

## BLANCOTHERM stainless steel

- With synthetic castors, corrosion-resistant in compliance with DIN 18867-8
- 125 mm dia., 2 fixed castors, 2 steering castors with locking brakes







### BLT stainless steel, convection-cooled

Illustration	Model	Designation	Capacity	Dimensions L x W x H (mm)	Rating/ conn. load	Weight (kg)	Order No.
	<b>BLT 1020 EUK</b>	<b>BLANCOTHERM 1020 EUK</b> Food transport container, convection-cooled, with hinged door, mobile, temperature range: +2 °C to +15 °C	GN container up to a max. of 3x GN 1/1-200 + 1x GN 1/1-100  14 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 845 x 1430 mm	220-240 V AC 50 Hz 0.3 kW	100 kg	<b>572 862</b>
	<b>BLT 1220 EUK</b>	<b>BLANCOTHERM 1220 EUK</b> Food transport container, convection-cooled, with hinged door, mobile, temperature range: +2 °C to +15 °C	GN container up to a max. of 5x GN 1/1-200  20 pairs of support ledges with spacing of 57.5 mm between ledges	540 x 845 x 1775 mm	220-240 V AC 50 Hz 0.3 kW	120 kg	<b>572 863</b>

## Accessories for BLANCOTHERM stainless steel

# accessories





### Accessories for all BLT stainless steel models

Illustration	Model	Designation	Dimensions L x W x H (mm)	Weight (kg)	Order No.
	<u>Eutectic plate</u>	<b>Eutectic plate</b> (-12 °C) of CNS, Gastronorm-compatible	530 x 325 x 30 mm	5.6 kg	<b>564 756</b>
	<u>Eutectic plate</u>	<b>Eutectic plate</b> (-3 °C) synthetic, Gastronorm-compatible	530 x 325 x 30 mm	4.2 kg	<b>568 136</b>
not shown	<u>Slide-in frame</u>	<b>Slide-in frame</b> of CNS 18/10 for Gastronorm containers up to 150 mm deep	530 x 325 x 156 mm		<b>564 352</b>
	<u>ST 3</u>	<b>GN support bar</b> of CNS 18/10 for container combination, required with GN 1/4, 1/6 and 1/9	Length: 325 mm		<b>550 650</b>
	<u>ST 5</u>	<b>GN support bar</b> of CNS 18/10 with spring lock, for container combination, required with GN 1/4, 1/6 and 1/9	Length: 530 mm		<b>550 651</b>

## Accessories for BLANCOTHERM stainless steel

# accessories

### Accessories for all BLT stainless steel models

Illustration	Model	Designation	Dimensions L x W x H (mm)	Weight (kg)	Order No.
	<u>Special pen</u>	<b>Special washable pen</b> for labeling menu cards			<b>564 361</b>
not shown	<u>Menu card holder</u>	<b>Menu card holder</b> for front side of door			
	<u>BLT E menu card</u>	<b>BLT E menu card</b> with hanging slot (blank)	DIN A6(148 x 105mm)		<b>572 513</b>
Menu card dispenser (shown with accessories: menu cards) 	<u>Menu card dispenser</u>	<b>Dispenser</b> for BLANCOTHERM menu cards, wire wall unit (Capacity: 50 cards)			<b>564 354</b>
Menu card box (shown with accessories: menu cards) 	<u>Menu card box</u>	<b>Menu card box</b> for BLANCOTHERM menu cards (Capacity: 25 cards)			<b>564 355</b>
not shown	<u>Push handle</u>	additional pull handle on back of unit	dia. 32 mm		

### Castor options for BLT stainless steel

Illustration	Model	Designation	For model
not shown	<u>Anti-static castors</u>	2 fixed and 2 steering castors with brakes, corrosion-resistant in compliance with DIN 18867-8, synthetic, <b>125 mm dia.</b>	all BLT E models
not shown	<u>Stainless-steel castors</u>	2 fixed and steering castors with brakes, <b>125 mm dia.</b>	all BLT E models
		2 fixed and 2 steering castors with brakes, <b>160 mm dia.</b> (in conjunction with 640 x 845 mm bottom plate)	all BLT E and BLT EB models
		2 fixed and 2 steering castors with brakes, <b>160 mm dia.</b> (in conjunction with 700 x 845 mm bottom plate)	BLT EUK
		2 fixed and 2 steering castors with brakes, with elastic castors, <b>160 mm dia.</b> (in conjunction with 640 x 845 mm bottom plate)	all BLT E and BLT EB models
		2 fixed and 2 steering castors with brakes, with elastic castors, <b>160 mm dia.</b> (in conjunction with 700 x 845 mm bottom plate)	BLT EUK
not shown	<u>Galvanized steel castors</u>	2 fixed and 2 steering castors with brakes, <b>160 mm dia.</b> (in conjunction with 640 x 845 mm bottom plate)	all BLT E and BLT EB models
		2 fixed and 2 steering castors with brakes, <b>160 mm dia.</b> (in conjunction with 700 x 845 mm bottom plate)	BLT EUK
		2 fixed and 2 steering castors with brakes, with elastic castors, <b>160 mm dia.</b> (in conjunction with 640 x 845 mm bottom plate)	all BLT E and BLT EB models
		2 fixed and 2 steering castors with brakes, with elastic castors, <b>160 mm dia.</b> (in conjunction with 700 x 845 mm bottom plate)	BLT EUK